

Application No.: 09/994,726
 Examiner: Truong, Lechi
 Art Unit: 2126

Applicant: Adlink Technology Inc.

IN THE CLAIMS

Please amend the claims as follows.

1. (previously presented) A control interface card connected to the CPU (central processing unit) of a host computer, adapted for auto-reloading object position data, comparing object position data, and providing a triggering signal to the CPU of the host computer, said control interface card comprising a data buffer adapted for registering a plurality of object position data computed by the CPU of said host computer, a position compare circuit adapted for fetching a registered object position data from said data buffer and comparing the fetched object position data with a feedback position data obtained via an object shifting control means, and then fetching a next registered object position data from said data buffer and comparing the next registered object position data with a feedback position data obtained via the object shifting control means, and a trigger I/O circuit adapted for providing a triggering signal to the CPU of said host computer when one of the registered position data is determined to match with one of the feedback position data by said position compare circuit.

2. (original) The control interface card as claimed in claim 1, which is a motion control interface card.

3. (original) The control interface card as claimed in claim 1, which is an industrial counting interface card.

4. (original) The control interface card as claimed in claim 1 further comprising a bus controller connected to a bus at the CPU of said host computer for intercommunication between the control interface card and the CPU of said host computer, and a bus arbitrator connected to said bus controller and adapted for providing an interrupt signal to the CPU of said host computer through said bus

Application No.: 09/994,726
Examiner: Truong, Lechi
Art Unit: 2126

Applicant: Adlink Technology Inc.

controller upon matching of one comparison at said position compare circuit.

5. (presently presented) A control interface card connected to the CPU (central processing unit) of a host computer, comprising:

a data buffer, for registering a plurality of object position data computed by the CPU of said host computer;

a comparing means, for sequentially fetching a registered object position data from said data buffer and comparing with a feedback position data obtained via an object shifting control means; and

a trigger I/O circuit, for providing a triggering signal to the CPU of said host computer when one of the registered position data is determined to match with one of the feedback position data by said position compare circuit.

6. (previously presented) The control interface card as claimed in claim 5, which is a motion control interface card.

7. (previously presented) The control interface card as claimed in claim 5, which is an industrial counting interface card.

8. (previously presented) The control interface card as claimed in claim 5 further comprising a bus controller connected to a bus at the CPU of said host computer for intercommunication between the control interface card and the CPU of said host computer, and a bus arbitrator connected to said bus controller and adapted for providing an interrupt signal to the CPU of said host computer through said bus controller upon matching of one comparison at said position compare circuit.